ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 092835 0081 Rev. 00

Holder of Attestation: **Suzhou Inovance Technology Co., Ltd.**
No. 52, Tian E Dang Road, Wuzhong District
215104 Suzhou City, Jiangsu Province
PEOPLE'S REPUBLIC OF CHINA

Product: **Electronic frequency converter (AC Drive)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105243184601

Date, 2025-03-24

(Kevin Liu)

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

TÜV SÜD Product Service GmbH • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®

ATTESTATION ◆ ATTESTATO ◆ ATTESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 092835 0081 Rev. 00

Model(s): **MD630S-4T9R0BS(a), MD630S-4T7R2BS(a), MD630S-4T5R1BS(a), MD630N-4T9R0BS(a), MD630N-4T7R2BS(a), MD630N-4T5R1BS(a)**

Remark:

"(a)" The model number may include a suffix "XXXXXXXXXX", where "XXXXXXXXXX" can be blank or combination of any alphanumeric and/or symbols that represents customer identity.

Brand: **INOVANCE**

INOVANCE

Parameters:

Construction: Built-in

Remark:

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area, and fire/mechanical protection enclosure shall be provided.
- For safe operation, a suitable external circuit breaker or fuse must be employed before installation.

Model No.	Rated Input	Rated Output
MD630S-4T9R0BS(a), MD630N-4T9R0BS(a)	3PH AC 380-480V 50/60Hz G: 11.4A, P: 17.0A	3PH AC 0-480V 0-599Hz 4kW G: 9.0A, P: 13.0A
MD630S-4T7R2BS(a), MD630N-4T7R2BS(a)	3PH AC 380-480V 50/60Hz G: 8.9A, P: 11.4A	3PH AC 0-480V 0-599Hz 3kW G: 7.2A, P: 9.0A
MD630S-4T5R1BS(a), MD630N-4T5R1BS(a)	3PH AC 380-480V 50/60Hz G: 6.3A, P: 9.0A	3PH AC 0-480V 0-599Hz 2.2kW G: 5.1A, P: 7.2A

Tested according to: EN 61800-5-1:2007/A11:2021

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

TÜV SÜD Product Service GmbH • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®