

B00
2026.05.12
正样


Amendment	Description

外部公开


Unit: mm









Standard accessories: A-type round head ordinary flat key
14x9x90 Refer to GB/T 1096




View A




View B



Service life	
Radial load (N)	Axial load (N)
Fr	Fa
3178	630



Nr	Specifications	Shape	Description
1	M4	Forked Type	Fan+
2	M4		Fan-
3	M10	Ring Type	U(red)
4	M10		V(yellow)
5	M10		W(blue)
6	M8		GND

Name	Definition of wiring for absolute value encoders							PT1000		
Definition	PS+ Yellow	PS- Yellow black	VB Battery+ Blue	VB Battery- Blue black	+5V Red	GND Black	Shielding layer	PT1000- White	PT1000+ Red	
17P Aviation connector	10	7	5	6	16	9	15	4	14	

				Motor Outline Drawing	0111B486-WX	
B00	New Archive	/	20260512			
Version	Change method	Changed by	Date			
Design	/			/	Mark	INOVANCE
Check	/					
Craft	/					
Verify	/			Weight	Scale	Version
Standardization	/			91.8kg	1:2	B00
Approve	/					

Page 1 Of 2

Model MEG23-41D17CD-A3A1F-CEN

Copyright: Copyright infringement reserved.

INOVANCE


A3

B00
2026.05.12
正样

Copyright: Copyright infringement reserved.

Amendment	Description

Basic function parameters		
Type	Unit	Value
Rated Torque	Nm	233
Rated Current	A	70.8
Peak Current	A	138
Rated Power	kW	41.4
Rated Speed	rpm	1700
Rate Frequency	Hz	113.33
Peak Torque	Nm	467
Max speed@380V	rpm	2600
Rated voltage	V	380
Rotor inertia	$kg \cdot cm^2$	375
Weight	kg	91.8
Stall Torque	Nm	279.6
Stall current	A	84.96
Duty	S1	



				Motor Outline Drawing	0111B486-WX	
A00	New Archive	/	20250717			
Version	Change method	Changed by	Date			
Design	/			/	Mark	INOVANCE
Check	/					
Craft	/					
Verify	/			Weight	Scale	Version	Page 2 Of 2
Standardization	/			91.8kg	1:2	B00	Model	MEG23-41D17CD-A3A1F-CEN
Approve	/					

INOVANCE

A3