

B00
2026.05.13
正样


Amendment	Description

外部公开


Unit: mm









Standard accessories: A-type round head ordinary flat key
14x9x90 Refer to GB/T 1096




View A



View B




Service life	
Radial load (N)	Axial load (N)
Fr	Fa
2584	490



Nr	Specifications	Shape	Description
1	M4	Forked Type	Fan+
2	M4		Fan-
3	M10	Ring Type	U(red)
4	M10		V(yellow)
5	M10		W(blue)
6	M8		GND

Name	Definition of wiring for absolute value encoders							PT1000		
Definition	PS+ Yellow	PS- Yellow black	VB Battery+ Blue	VB Battery- Blue black	+5V Red	GND Black	Shielding layer	PT1000- White	PT1000+ Red	
17P Aviation connector	10	7	5	6	16	9	15	4	14	



B00	New Archive	/	20260513	Motor Outline Drawing	0111B510-WX	
Version	Change method	Changed by	Date			
Design	/			/	Mark	INOVANCE
Check	/					
Craft	/					
Verify	/			Weight	Scale	Version
Standardization	/			115.8kg	1:2	B00
Approve	/					

Page 1 Of 2

Model: MEG23-63D22CD-A3A1F-CEN

Copyright: Copyright infringement reserved.

INOVANCE

A3


B00
2026.05.13
正样

Copyright: Copyright infringement reserved.

Amendment	Description

外部公开

Basic function parameters		
Type	Unit	Value
Rated Torque	Nm	270
Rated Current	A	112.5
Peak Current	A	202.5
Rated Power	kW	62.2
Rated Speed	rpm	2200
Rate Frequency	Hz	146.67
Peak Torque	Nm	546
Max speed@380V	rpm	3000
Rated voltage	V	380
Rotor inertia	$kg \cdot cm^2$	479
Weight	kg	115.8
Stall Torque	Nm	324
Stall current	A	135
Duty	S1	



				Motor Outline Drawing			0111B510-WX
B00	New Archive	/	20260513				
Version	Change method	Changed by	Date				
Design	/			/			Mark
Check	/						
Craft	/						
Verify	/			Weight	Scale	Version	Page 2 Of 2
Standardization	/			115.8kg	1:2	B00	Model MEG23-63D22CD-A3A1F-CEN
Approve	/						

INOVANCE

A3