
正样
2025.09.30


Copyright:Copyright infingmengt reserved

| 修订 | 说明 |
|---|---|
| | |


外部公开


Unit: Millimeter (mm)








| Basic function parameters | |
|---|---|
| Rated power KW | 0.75 |
| Rated voltage V | 220 |
| Rated current A | 4.4 |
| Peak current at rated speed A | 16.9 |
| Rated torque Nm | 2.39 |
| Peak torque at rated speed Nm | 8.36 |
| Rated speed rpm | 3000 |
| Max speed rpm | 7000 |
| Rotor inertia kg · cm2 | 0.68±10% |
| Encoder resolution | 26bit |
| Insulation class | F(155) |
| Protection level | IP67 |
| Static torque of brake Nm | / |
| Brake power supply | / |
| Duty cycle | S1 |
| Radial load N | ⩽392 |
| Axial load N | ⩽147 |





Dimension of shaft end




Dimension of shaft end with key



| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | Motor Outline Drawing | 0111BA76-WX | |
| B00 | New Archive | / | 20250926 | | | |
| Version | Change method | Changed by | Date | | | |
| Design | / | | | | Mark | INOVANCE |
| Check | / | | | | | |
| Craft | / | | | | | |
| Verify | / | | | Weight | Scale | Version | Page 1 of 1 |
| Standardization | / | | | 2.22kg | 1:1 | B00 | Model | MS1H1-75B30CB-V631R-INT |
| Approve | / | | | | | |

INOVANCE

A3