
正样
2026.08.26
B00


All rights reserved. Any infringement will be prosecuted.


Inovance Technology Co., Ltd.

Revise	Description

外部公开









Definition of power cable connection			
Terminal①	Phase U	Phase V	Phase W
Sign	U	V	W


Definition of power cable connection			
Terminal②	Band-type brake BK+	Band-type brake BK-	Ground connection
Sign	1	2	M5 screw hole of binding post

Wiring definition of signal cable									
Terminal②	PS+	PS-	BT-	BT+	+5V	GND	PE	PTC+	PTC-
Sign	3	4	5	6	7	8	9	10	11


Basic function parameters	
Rated power kW	4.5
Rated voltage V	380
Rated current A	15
Peak current at rated speed A	65
Rated torque Nm	29
Peak torque at rated speed Nm	119
Rated speed rpm	1500
Max speed rpm	4500
Rotor inertia kg · cm^2	127.5±10%
Encoder resolution	23bit
Insulation class	F(155)
Protection class	IP66/IP67
Static torque of brake Nm	/
Brake power supply V	/
Brake backlash°	/
Duty cycle	S1
Radial load N	⩽1764
Axial load N	⩽588








Axis end dimension diagram



Dimension diagram of shaft end with key



				Outline drawing of the whole machine	0111BJ44-WX		
B00	New Archive	/	2026.01.14				
Version	Alter mode	Changer	Date				
Design	/			/	Projection mark	INOVANCE	
Proofread	/						
Technological	/						
Check	/			Weight	Ratio	Version	The first page one page in total
Standardization	/			34.8kg	1:2	B00	Product: MS1H3-45C15□-A331R-INT-EX d T5
Approve	/						

A3