

正样
2026.08.26
300


All rights reserved. Any infringement will be investigated.


外部公开

Revise	Description












Terminal connector definition




Basic function parameters	
Rated power Kw	0.4
Rated voltage V	220
Rated current A	2.4
Peak current at rated speed A	9.2
Rated torque Nm	1.27
Peak torque at rated speed Nm	4.45
Rated speed rpm	3000
Max speed rpm	7000
Rotor inertia kg · cm2	0.45±10%
Encoder resolution	23bit
Insulation Class	F
Protection class	IP66/IP67
Static torque of brake Nm	≥1.5
Brake power supply V	DC24V±10%
Brake backlash °	≤1
Duty cycle	S1
Radial load N	≤245
Axial load N	≤74





Axial end dimension drawing
Axial end dimension drawing with key



Ratio 0.400

				Outline drawing of the whole machine			0111BJ78-WX
B00	New Archive	/	20260309				
Version	Alter mode	Changer	Date				
Design	/			/			Projection mark
Proofread	/						
Technological	/						
Check	/			Weight	Ratio	Version	The first page one page in total
Standardization	/			kg	1:2	B00	Product MS1H4-40B30CB-A334R-INT-EX d T5
Approve	/						

INOVANCE

Inovance Technology Co., Ltd.

A3